



816 W. Barbours Cut Blvd.
 LaPorte, TX 77571
 Sales: 713-460-3960
www.NationalChassis.com

DOUBLE DROP FRAME AIR RIDE TANK CHASSIS

GENERAL PARAMETERS	
Tare Weight	Approximately 10,700 lbs
GVWR	61,000 LBS
Conspicuity	Meets DOT requirements
Main Beams	Fabricated I-beam
Front, Rear Bolsters	6 in x 8 in structural tubing with buffers, twist locks
Mud Flaps	Plastic anti-sail
Overall Chassis Width, Length	102 in x 42'
Fifth Wheel Height	48 in
Light Attachment, Type	12v truck-lite flange mounted LED
LANDING GEAR	
Landing Gear	Two speed AAR approved, square leg. 55,000 lb lift capacity and 160,000 static load capacity
Landing Gear Foot Group	10 in. by 10 in. low profile sandshoe
Lift Device	Lift ready, but not included
Hi-Lo Kit	Hi-Lo ready, but not included
Crank Handle Location	Road side handle
BRAKES	
Drum	Outboard mounted
Brake Lining Options	R23
System Type	2S1M
WHEELS	
Rims	8 1/4 x 22.5 hub piloted, white
Tires	11R x 22.5
AXLES	
Axle Quantity	2 Axles
Axle Locations	49 1/2 in from rear
Kingpin Location	15 in from front of chassis
SUSPENSION	
Suspension Type	Air Ride
FINISH	
Metal Preparation	Clean, dry steel and NACE No. 3 /SSPC-SP-6 "Commercial Blast Cleaning"
Primer	70% Zinc Rich Primer
Topcoat	Urethane
Color	Black