



816 W. Barbours Cut Blvd.
 LaPorte, TX 77571
 Sales: 713-460-3960
www.NationalChassis.com

SPREAD AXLE TANK CHASSIS

GENERAL PARAMETERS

Tare Weight	Approximately 7,325 lbs
GVWR	80,000 LBS
Conspicuity	Meets DOT requirements
Main Beams	Fabricated grade 130 material tapered at rear
Upper Coupler Assembly	Pick up plate is 5/16 in thick and extends approximately 18 in behind the kingpin and is reinforced fore and aft by 5/16 in formed channels
Front Bolster	Fabricated channel
Rear Bolster	Fabricated channel
Mud Flaps	Plastic anti-sail
Overall Chassis Width, Length	96" x 43' 6"
Light Attachment, Type	Flange mounted, LED

LANDING GEAR

Landing Gear	Two speed AAR approved, square leg. 55,000 lb lift capacity and 160,000 static load capacity
Landing Gear Foot Group	10 in. by 10 in. low profile sandshoe
Lift Device	Lift ready, but not included
Hi-Lo Kit	Hi-Lo ready, but not included
Crank Handle Location	Road side handle

BRAKES

Drum	Outboard mounted
Brake Lining Options	High capacity 23,000
System Type	2S1M

WHEELS

Rims	8 1/4 x 22.5 hub piloted tubeless
Tires	11R 22.5

AXLES

Axle Quantity	2 Axles
Axle Centers	109 in
Kingpin Location	15 in

SUSPENSION

Suspension Type	Spring Ride, Three Leaf (24K HD)
-----------------	----------------------------------

FINISH

Metal Preparation	Clean, dry steel and NACE No. 3 /SSPC-SP-6 "Commercial Blast Cleaning"
Primer	70% Zinc Rich Primer
Topcoat	Urethane
Color	Black